



## SLP355S-24D SLP360S-24D SLP365S-24D SLP370S-24D

### Electric Performance Parameters

TYPE	SLP355S-24D	SLP360S-24D	SLP365S-24D	SLP370S-24D
Rated power (W)	355W	360W	365W	370W
Deviation of rated power (W)	0~+5W	0~+5W	0~+5W	0~+5W
Optimum operating voltage (Vmp)	38.51V	38.71V	38.96V	39.24V
Optimum operating current (Imp)	9.22A	9.30A	9.37A	9.43A
Open-circuit voltage (Voc)	46.94V	47.19V	47.49V	47.83V
Short-circuit current (Isc)	9.68A	9.77A	9.84A	9.90A
Temperature coefficient of open-circuit voltage		-0.36%/°C		
Temperature coefficient of short-circuit current		-0.07%/°C		
Temperature coefficient of rated power		-0.38%/°C		
Standard operating temperature		45±2°C		

STC: illumination intensity: 1000W/M<sup>2</sup>, battery temperature: 25°C, air quality=1.5

NOCT: illumination intensity: 800W/M<sup>2</sup>, environmental temperature: 20°C, air quality=1.5, wind speed: 1m/s

### Packaging Information

Type of Cell	Monocrystalline silicon cell (156.75x78.375)
Cell Array	144 (6x24)
Module Dimension	1988mm x 992mm x 40mm
Weight	22.3kg
Pallet Dimension	2036mm x1120mm x 1130mm(26 pieces/pallet)
Container loading information (40HQ)	572 pieces

### Operation Condition

Maximum system voltage	1000V
Rated current of serial fuse	15A
Maximum front load	5400Pa (112 lb/ft <sup>2</sup> )
Maximum back load	2400Pa (50 lb/ft <sup>2</sup> )
Operating temperature range	-40~+85°C
Module Standard	A

### Module Dimension: (unit: mm)

